

AMENDMENTS TO THE CLAIMS

Please amend claims 1, 12, 28 and 41. Please cancel claims 6, 16, 29, 45 and 47-53. Following is a listing of the claims, as amended.

1. (Currently Amended) An apparatus for handling microelectronic workpieces, comprising:

an input/output station configured to removably receive microelectronic workpieces at an input/output location;

a pre-process station configured to identify and/or align the microelectronic workpieces, the pre-process station including a first workpiece support positioned to carry a microelectronic workpiece;

a storage station having a plurality of second workpiece supports, with each second workpiece support being positioned to carry a microelectronic workpiece before processing, after processing or both before and after processing, wherein the first and second workpiece supports are positioned to support coaxially located microelectronic workpieces;

at least one process station spaced apart from the pre-process station and the input/output station;

a first transfer device movably positioned proximate to the input/output station, the first transfer device being configured to move the microelectronic workpieces directly between the input/output location and the pre-process station; and

a second transfer device movably positioned proximate to the at least one process station, the second transfer device being configured to move the microelectronic workpieces directly between the pre-process station and the at least one process station.

2. (Original) The apparatus of claim 1, further comprising an enclosure having at least one aperture and being disposed at least partially around the at least one process

station, and wherein the input/output station is configured to receive microelectronic workpieces through the at least one aperture in the enclosure.

3. (Original) The apparatus of claim 1 wherein the first transfer device includes a first automatic robot and the second transfer device includes a second automatic robot.

4. (Original) The apparatus of claim 1, further comprising a storage station having a plurality of workpiece supports, with each workpiece support being positioned to carry a microelectronic workpiece before processing, after processing or both before and after processing, wherein at least a portion of one of the pre-process station and the storage station overlaps at least a portion of the other of the pre-process station and the storage station.

5. (Original) The apparatus of claim 1, further comprising a storage station having a plurality of workpiece supports, with each workpiece support being positioned to carry a microelectronic workpiece before processing, after processing or both before and after processing, and wherein the storage station and the pre-process station together form a transfer station.

6. (Cancelled)

7. (Original) The apparatus of claim 1 wherein the input/output station includes a plurality of container supports, with each container support configured to releasably carrier a container of microelectronic workpieces.

8. (Original) The apparatus of claim 1 wherein the pre-process station is one of at least two pre-process stations, and wherein the first transfer device is one of at least two first transfer devices.

9. (Original) The apparatus of claim 1 wherein the pre-process station includes a sensor positioned to detect an identifying characteristic of the microelectronic workpieces.

10. (Original) The apparatus of claim 1 wherein the at least one process station is configured to apply a conductive material to the microelectronic workpieces.

11. (Original) The apparatus of claim 1 wherein the at least one process station includes at least one of a metrology station, a material application station, a cleaning station, an etching station and an annealing station.

12. (Currently Amended) An apparatus for processing microelectronic workpieces, comprising:

at least one process station configured to carry a microelectronic workpiece during processing;

a pre-process station configured to identify and/or align the microelectronic workpiece, the pre-process station including a first workpiece support positioned to carry a microelectronic workpiece; and

a storage station having a plurality of second workpiece supports, with each second workpiece support being positioned to carry a microelectronic workpiece before processing, after processing or both before and after processing, wherein the first and second workpiece supports are positioned to support coaxially located microelectronic workpieces~~at least a portion of one of the pre-process station and the storage station overlaps at least a portion of the other of the pre-process station and the storage station.~~

13. (Original) The apparatus of claim 12 wherein each workpiece support includes a plurality of support posts, and wherein each support post includes a contact surface positioned to contact a peripheral region of the microelectronic workpiece.

14. (Original) The apparatus of claim 12, further comprising:
an enclosure having at least one aperture and being disposed at least partially around the at least one process station; and
an input/output station configured to receive microelectronic workpieces through the at least one aperture in the enclosure.
15. (Original) The apparatus of claim 12, further comprising:
an input/output station configured to removably receive a plurality of microelectronic workpieces at an input/output location;
a first transfer device movably positioned proximate to the input/output station, the first transfer device being configured to move the microelectronic workpieces directly between the input/output location and the pre-process station; and
a second transfer device movably positioned proximate to the at least one process station, the second transfer device being configured to move the microelectronic workpieces directly between the pre-process station and the at least one process station.
16. (Cancelled)
17. (Original) The apparatus of claim 12 wherein the pre-process station is one of at least two pre-process stations and wherein the storage station is one of at least two storage stations.
18. (Original) The apparatus of claim 12 wherein the pre-process station includes a sensor positioned to detect an identifying characteristic of the microelectronic workpiece.
19. (Original) The apparatus of claim 12 wherein the at least one process station is configured to apply a conductive material to the microelectronic workpiece.

20. (Original) An apparatus for handling microelectronic workpieces, comprising:
at least one process station configured to carry a microelectronic workpiece during processing;
a pre-process station configured to identify and/or align microelectronic workpieces at a first workpiece location with the microelectronic workpieces in a first workpiece plane; and
a storage station having a plurality of workpiece supports, each positioned to carry a microelectronic workpiece in a corresponding second workpiece location with the microelectronic workpiece in a second workpiece plane before processing, after processing or both before and after processing the microelectronic workpiece, wherein the first and second workpiece locations are coaxial along an axis generally normal to at least one of the workpiece planes.

21. (Original) The apparatus of claim 20 wherein the workpiece supports are first workpiece supports positioned to carry a first microelectronic workpiece centered on the axis, and wherein the pre-process station includes a second workpiece support configured to carry a second microelectronic workpiece centered on the axis.

22. (Original) The apparatus of claim 20 wherein each workpiece support includes a plurality of support posts, and wherein each support post includes a contact surface positioned to contact a peripheral region of the microelectronic workpiece.

23. (Original) The apparatus of claim 20, further comprising:
an enclosure disposed at least partially around the at least one process station; and
an input/output station configured to receive microelectronic workpieces through an aperture in the enclosure.

24. (Original) The apparatus of claim 20, further comprising:
an input/output station configured to removably receive microelectronic workpieces at an input/output location;
a first transfer device movably positioned proximate to the input/output station, the first transfer device being configured to move the microelectronic workpieces directly between the input/output location and the pre-process station; and
a second transfer device movably positioned proximate to the at least one process station, the second transfer device being configured to move the microelectronic workpieces directly between the pre-process station and the at least one process station.

25. (Original) The apparatus of claim 20 wherein the pre-process station is one of at least two pre-process stations and wherein the storage station is one of at least two storage stations.

26. (Original) The apparatus of claim 20 wherein the pre-process station includes a sensor positioned to detect an identifying characteristic of the microelectronic workpiece.

27. (Original) The apparatus of claim 20 wherein the at least one process station is configured to apply a conductive material to the microelectronic workpiece.

28. (Currently Amended) An apparatus for handling microelectronic workpieces, comprising:

at least one process station configured to carry a microelectronic workpiece during processing;
a pre-process station configured to identify and/or align microelectronic workpieces, the pre-process station having a first footprint; and

a storage station having a plurality of workpiece supports, with each workpiece support being positioned to carry a microelectronic workpiece before processing, after processing or both before and after processing the microelectronic workpiece, the storage station having a second footprint, wherein at least a portion of at least one of the first and second footprints overlaps at least a portion of the other of the first and second footprints, and wherein the workpiece supports are first workpiece supports positioned to carry first microelectronic workpieces centered on an axis, further wherein the pre-process station includes a second workpiece support configured to carry a second microelectronic workpiece centered on the same axis.

29. (Cancelled)

30. (Original) The apparatus of claim 28 wherein each workpiece support includes a plurality of support posts, and wherein each support post includes a contact surface positioned to contact a peripheral region of the microelectronic workpiece.

31. (Original) The apparatus of claim 28, further comprising:
an enclosure disposed at least partially around the at least one process station; and
an input/output station configured to receive microelectronic workpieces through an aperture in the enclosure.

32. (Original) The apparatus of claim 28, further comprising:
an input/output station configured to removably receive a plurality of microelectronic workpieces at an input/output location;
a first transfer device movably positioned proximate to the input/output station, the first transfer device being configured to move the microelectronic workpieces directly between the input/output location and the pre-process station; and

a second transfer device movably positioned proximate to the at least one process station, the second transfer device being configured to move the microelectronic workpieces directly between the pre-process station and the at least one process station.

33. (Original) The apparatus of claim 28 wherein the pre-process station is one of at least two pre-process stations and wherein the storage station is one of at least two storage stations.

34. (Original) The apparatus of claim 28 wherein the pre-process station includes a sensor positioned to detect an identifying characteristic of the microelectronic workpiece.

35. (Original) The apparatus of claim 28 wherein the at least one process station is configured to apply a conductive material to the microelectronic workpiece.

36. (Original) An apparatus for handling microelectronic workpieces, comprising:
a plurality of workpiece processing stations;
an enclosure at least partially enclosing the plurality of workpiece processing stations;
an input/output station configured to removably receive microelectronic workpieces at an input/output location from a region external to the enclosure;
a pre-process station configured to identify and/or align microelectronic workpieces at a first workpiece location, the pre-process station having a first footprint;
a storage station having a plurality of workpiece supports, with each workpiece support being positioned to carry a microelectronic workpiece at a second workpiece location before processing, after processing or both before and after processing the microelectronic workpiece, the storage station having a second footprint, wherein at least a portion of at least one of the first and

second footprints overlaps at least a portion of the other of the first and second footprints and wherein the first and second workpiece locations are coaxial;

a first transfer device movably positioned proximate to the input/output station, the first transfer device being configured to move microelectronic workpieces directly between the input/output location and the pre-process station, the first transfer device further being configured to move microelectronic workpieces directly between the input/output location and the storage station; and

a second transfer device movably positioned proximate to the process stations, the second transfer device being configured to move the microelectronic workpieces directly between the pre-process station and the at least one process station.

37. (Original) The apparatus of claim 36 wherein each workpiece support includes a plurality of support posts, and wherein each support post includes a contact surface positioned to contact a peripheral region of the microelectronic workpiece.

38. (Original) The apparatus of claim 36 wherein the pre-process station is one of at least two pre-process stations and wherein the storage station is one of at least two storage stations.

39. (Original) The apparatus of claim 36 wherein the pre-process station includes a sensor positioned to detect an identifying characteristic of the microelectronic workpiece.

40. (Original) The apparatus of claim 36 wherein the at least one process station is configured to apply a conductive material to the microelectronic workpiece.

41. (Currently Amended) An apparatus for handling microelectronic workpieces, comprising:

an input/output station configured to removably receive microelectronic workpieces at an input/output location;

a storage station spaced apart from the input/output location and configured to carry a plurality of microelectronic workpieces, the storage station including a plurality of first workpiece supports positioned to carry a plurality of microelectronic workpieces;

at least one process station spaced apart from the storage station and the input/output station;

a pre-process station configured to identify and/or align a microelectronic workpiece, the pre-process station further having a second workpiece support, and wherein the first and second workpiece supports are positioned to carry microelectronic workpieces coaxially;

a first transfer device movably positioned proximate to the input/output station, the first transfer device being configured to move the microelectronic workpieces directly between the input/output location and the storage station; and

a second transfer device movably positioned proximate to the at least one process station, the second transfer device being configured to move the microelectronic workpieces directly between the storage station and the at least one process station.

42. (Original) The apparatus of claim 41, further comprising an enclosure having at least one aperture and being disposed at least partially around the at least one process station, and wherein the input/output station is configured to receive microelectronic workpieces through at least one aperture in the enclosure.

43. (Original) The apparatus of claim 41 wherein the first transfer device includes a first automatic robot and the second transfer device includes a second automatic robot.

44. (Original) The apparatus of claim 41, further comprising a pre-process station configured to carry a microelectronic workpiece and identify and/or align the microelectronic workpiece, wherein at least a portion of one of the pre-process station and the storage station overlaps the other of the pre-process station and the storage station.

45. (Cancelled)

46. (Original) The apparatus of claim 41 wherein the at least one process station is configured to apply a conductive material to the microelectronic workpiece.

47-59. (Cancelled)